



CODE: PTS-KB-6X050-B2R
DESCRIPTION: Temperature Sensor PT1000 Class B, AISI316 sheath, Ø 6 mm, M12, Transmitter 4..20 mA

POWER SUPPLY: 12..24V DC ± 10%
OPERATING TEMPERATURE: -50°C / +150°C (range)
IMMERSED MATERIAL: Steel AISI 316L (food grade)
FITTING MATERIAL: N.A.
SENSOR INSULATION: MgO Magnesium Oxide >20Mohm @ 25°C (500VDC)
TIP TAPERING: NO
CERTIFICATION: NO

TOTAL LENGTH (E): 50 mm
SHEATH EXT. Ø (S): 6 mm
SHEATH INT. Ø: 5 mm
RTD RESPONSE: 7,5 sec
COMPLIANCE



PIN1 (+) = VCC
 PIN2 (-) = OUT

°C	OUT (mA)
-50	4
50	12
+150	20




T. MAX 150° C

Insulation: >20 MOhm @ 25° C
 (500 VDC)

GENERAL TOLERANCE EN 22768-m	DRAWER: Matteo Cardi	PROD. CODE:
LINEAR DIMENSION: mm	CONTROL: Daniele Longhin	PTS-KB-6X050-B2R
UNAUTHORIZED REPRODUCTION FORBIDDEN	DRAWING/ED.: PTS_0021	DESCRIPTION: PT1000B, AISI316, Ø 6 mm, M12, Tr. 4..20 mA, -50/150 C°
	REV./DATE: 00 / 30/01/2024	

STANDARD DIN EN 60751

Temperature C°	Tolerance PT1000 B Class (+/- C°)
-200	1.3
-100	0.8
0	0.3
100	0.8
200	1.3
300	1.8
400	2.3
500	2.8




RTD response time with steel tube AISI-316/304 MgO insulated, conforming to B.S. 1904/1984/CEI60751. 50mm immersion in water at a speed of 1m/sec. Calculated on 63.2 % of the thermal jump, depending on stem diameter and thickness.

Pixsys srl
 Via Po, 16
 30030 - Mellaredo di Pianiga
 Venezia - Italia
 Tel. +39 041 5190518
 Fax +39 041 519002
 Mail info@pixsys.net
 www.pixsys.net



Manual's code: 2300.10.373
 Document version: rel.01
 Last update: 10/12/2024
 Author: Matteo Cardi

Ordering Code:

Sensor type	
1B	PT100 CLASS B
KA	PT1000 CLASS A
KB	PT1000 CLASS B
5A	PT500 CLASS A
PK	PTC 1000 OHM
P2	PTC 120 OHM
N1	NTC 10K (β 3435K)
N2	NTC 10K (β 3694K)
N3	NTC 2252 (β 3976K)
TH	NI100
I2	NI120
TK	THERMOCOUPLE K
TJ	THERMOCOUPLE J
TS	THERMOCOUPLE S

Sheath diameter and length (S x L)	
Examples:	
6X050	Ext. Ø 6 mm x 50 mm
6X100	Ext. Ø 6 mm x 100 mm
6X200	Ext. Ø 6 mm x 200 mm
6X400	Ext. Ø 6 mm x 400 mm
8X250	Ext. Ø 8 mm x 250 mm
4X050	Ext. Ø 4 mm x 50 mm
AX150	Ext. Ø 10 mm x 150 mm
6X1M0	Ext. Ø 6 mm x 1 m
8X1M5	Ext. Ø 8 mm x 1,5 m
...	

Process connection	
Examples:	
0	NN
1	1/8" MALE GAS FIXED UNDERHEAD
2	1/4" MALE GAS FIXED UNDERHEAD
3	1/2" MALE GAS FIXED UNDERHEAD
4	1" MALE GAS FIXED UNDERHEAD
...	
6	1/8" MALE NPT GAS FIXED UNDERHEAD
7	1/4" MALE NPT GAS FIXED UNDERHEAD
8	1/2" MALE NPT GAS FIXED UNDERHEAD
9	1" MALE NPT GAS FIXED UNDERHEAD
...	
A	1/8" MALE GAS SLIDING
B	1/4" MALE GAS SLIDING
C	1/2" MALE GAS SLIDING
D	1" MALE GAS SLIDING

Sheath material	
A	STEEL AISI304 SHEATH
B	STEEL AISI316 SHEATH
C	STEEL AISI308 SHEATH
M	STEEL AISI304 SHEATH, MgO INSULATION
N	INCONELL600 SHEATH
K	SINGLE CERAMIC SHEATH
Y	DOUBLE CERAMIC SHEATH

Head/Cable/Connector	
Examples:	
A	HEAD DIN A
B	HEAD DIN B
C	HEAD MINI DIN
T	HEAD DIN A ATEX
X	HEAD DIN B ATEX
Y	HEAD MINI DIN ATEX
M	CONNECTOR M12 4 PIN
R	CONN. M12 4 PIN + TRANSM. 4..20 mA / -50..+150 °C
V	CONN. M12 4 PIN + TRANSM. 0..10 V / 0..+150 °C
W	CONN. M12 4 PIN + TRANSM. 0..10 V / -100..+100 °C
...	
1	GSC SILICONE CABLE 2m
2	PVC CABLE 2m
3	TTS CABLE 2m
4	SPECIAL CABLE 2m
5	GSC SILICONE CABLE 3m
6	PVC CABLE 3m
7	TTS CABLE 3m
8	SPECIAL CABLE 3m
9	FREE
Z	CUSTOM

Suggested cables:



CODE:

CAB-M12FD5A3R

PVC 5 poles M12 female straight cable



CODE:

CAB-M12FA5A3R

PVC 5 poles M12 female angled cable

OPERATING TEMPERATURE: -25°C / +80°C

HOUSING / MOLDED BODY: TPU

INSERT:

CONTACT: CuSn pre-nickeled and 0.3 microns gold-plated

KNURLED SCREW:

O-RING:

PROTECTION DEGREE: IP67 in locked position

CONTACT RESISTANCE: $\leq 5 \text{ m}\Omega$

NOMINAL CURRENT AT 40°C: 4 A

NOMINAL/RATED VOLTAGE: 240 V / 250 V

TEST VOLTAGE: 2.0 kV eff. /60 s

INSULATION RESISTANCE: $> 10^9 \Omega$

POLLUTION DEGREE:

3